

Fixed Wireless Phone 21G



GSM

GPRS

SMS

Overview

The VISIONTEK 21G GSM Desk Phone allows users access to voice calls communication on GSM mobile phone network with a SIM Card. Our FWP combines simplicity with advanced features.

VISIONTEK 21G GSM Desk Phone enables instant telephone access to various applications like providing a landline alternative for remote areas, ships, vehicles, construction, oil and mining companies, exhibitions, disaster recovery service or any temporary sites.

VISIONTEK 21G is available in two colors White & Black and also with PCO billing features.

Voice & GPRS*

Built-in Battery & Charger

PCO / Payphone

Application Areas

- Business Houses with Multiple Locations
- Telecom Service Providers
- News Agencies
- Broadcasting Companies
- Event Management Organizations
- Law Enforcement Agencies
- Community Phones
- SOHO Applications
- Residential Applications
- Call shops / Teleboutiques / Bureaus
- PCO / Payphone



22 Keys Multi-function Keypad



128x64 Graphic LCD

Visit : www.visiontek.co.in
for other products

Instant Voice and SMS

Dual-band* GSM 900 / 1800 Mhz



Benefits

- Immediate primary telephone access
- Savings on GSM call costs
- 128 x 64 Graphic LCD with backlight
- Payphone* applications
- Minimized RF hazards
- Operator specific security locks

Features

- Desktop speaker phone with superior voice quality
- Built in echo-canceller
- Short Messages Services (SMS) and Internet*
- Redial last number or from list
- Call duration, Day, Date & Time display
- Network selection – Automatic & Manual
- Programmable local area code
- Call barring (Local, STD & ISD)
- Buzzer indication on call disconnection
- Built-in alarm function
- Built-in calculator
- Call log details
- 250 numbers phone book memory
- Fixed and on-hook dialing
- LED indication: Power, Network
- Polyphonic / Mono ring tones
- PSTN dial tone
- Caller ID
- PCO option
- OTA configuration
- Multi Conference

Specifications

LCD Display	Dimension – 128 x 64 Number of Lines – 04, (Number of Characters Per Line – 21)
Network Frequency	Dual Band GSM 900/1800 MHZ
Receiver Sensitivity	-107dB
Keypad	22 keys for multi functional operation
Input Voltage	AC 100 – 300V (50Hz to 60Hz) DC output (i) Battery : 13.8V DC output (ii) Load : 9.5V , 1A
Battery Charger	Built-in
Time for Charging	6-8 Hours
Battery Type	3.6v Ni-Mh 1200mAh
Talk Time	** 3 Hours
Stand By Time	** 72 Hours
Enclosure	ABS Plastic
Humidity	Operating : 10% ~ 90% Storage : 5% ~ 95%
Interface	User friendly Programming Power, Network, Signal Strength, Date & Time indication RJ45 connector for Software Downloading DC power supply socket SIM Socket Soft key ON/OFF SMA antenna connector
Temperature	Operating : -10°C to +55°C Storage : -20°C to +60°C
Dimensions in mm	220 x 204 x 79 (L x W x H)
Weight	800 grams
Antenna	3dB di-pole antenna

Note: We pursue a policy of continuous research and product development. Specifications and features are subject to change without notice

* Indicates optional feature
** Conditions Apply

